

MUG

Lounge

Single pendant



Spec sheet

LG-01-P

Lounge

Single pendant

GLASS FINISH Champagne
Steel gray
Light gray
Opal white
Satinated Champagne
Satinated Steel gray
Satinated Light gray

STRUCTURE FINISH Matte black
Pewter

MATERIALS:

INNER DIFFUSER Aluminum

OUTER DIFFUSER PMMA

STEM Mouth-blown glass

LIGHT SOURCE INTEGRATED LED MODULE 10W 24V
3000°K 1400lm CRI 90+

VOLTAGE 220 - 240V 50Hz
120V 60Hz

DRIVER ON-OFF (standard)
Dimmable on request

ENVIRONMENT Indoor

CERTIFICATION  UL WIRED  IP20



Product nomenclature of standard variation (custom solutions are available on request)

LG		O1		P		P		CH		D		E		1	
Family		Version		Model		Body color		Glass color				Input		CCT	
LG	Lounge	01	1x	P	Pendant	PW	Pewter	CH	Champagne	D	DALI	E	230V 50Hz	1	3000°K
		03	3x	W	Wall	MB	Matte black	LG	Light gray	1	On/off	U	120V 60Hz	2	2.700°K
		03	3x	C	Chandelier			SG	Steel gray	0	0-10V				
		04	4x	L	Linear chandelier			SC	Satin champagne	T	Triac				
		06	6x					SS	Satin steel gray						
								SL	Satin light gray						
								OW	Opal White						